



> PRINT > COPY > SCAN

TASKalfa 1800
TASKalfa 2200

B/W MULTIFUNCTIONALS
FOR A3 FORMAT

THE COMPACT BUT THOROUGH BUSINESS COMPANION.



Designed to be as easy to use as possible, a TASKalfa 1800 or 2200 MFP will significantly simplify your business workflow. From the durability of its components to the intuitive design of the control panel, every part of the device has been designed to provide exceptional reliability and increase efficiency. This compact device is very easy to operate and will speedily deliver the professional quality that your business demands, whether you need to print, copy or scan.

- > Up to 18/22 pages A4 and 8/10 pages A3 per minute
- > Standard print and colour scan functionality
- > ID card copy function
- > 600 dpi laser technology with 256-greyscale copying for crisp text and realistic photos
- > Optional duplex unit for cost-saving double-sided printing
- > Optional 50-sheet reversing document processor
- > Standard paper capacity of 400 sheets (expandable to 1,300 sheets)
- > Long-life components for exceptional efficiency and reliability



The TASKalfa 1800/2200 incorporates extremely durable components that guarantee efficient and reliable operation, to meet the demanding requirements of busy office environments. These devices provide effective productivity and maximum flexibility whilst ensuring minimum impact on the environment.

GENERAL

Technology

KYOCERA Laser, Mono component

Engine speed (pages per minute)

TASKalfa 1800: Max. 18/8 pages per minute A4/A3

TASKalfa 2200: Max. 22/10 pages per minute A4/A3

Resolution: 600 x 600 dpi, 256 greyscales

Warm-up time from power on

17.2 seconds or less from power on

Time to first page: 5.7 seconds or less

Dimensions (W x D x H): 565 x 527 x 485 mm

Weight: Main unit: approx. 26 kg

Power source: AC 220 ~ 240 V, 50/60 Hz

Power consumption

TASKalfa 1800:

Printing: 385 W

Standby: 75 W

Sleep mode: 1,54 W

TASKalfa 2200:

Printing: 415 W

Standby: 76 W

Sleep mode: 1,54 W

Noise (sound pressure level ISO 7779/ISO 9296)

Copying: 62.0 dB(A); standby: 40 dB(A)

Safety standards: GS, TÜV, CE

This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard

PAPER HANDLING

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity

300-sheet universal paper cassette, 64–105 g/m², A3, A4, A5, Ledger, Letter, Legal

100-sheet multi-purpose tray, 45–160 g/m², A3, A4, A5, A6, Ledger, Letter, Legal

Max. input capacity with options: 1,300 sheets

Output capacity: 250 sheets face-down

PRINT FUNCTIONS

CPU: ARM v5 base core equivalent, 500 MHz

Memory: standard max. 256 MB

Emulations: Host-based printing system for all current windows operating systems

Standard Interface: USB 2.0 (Hi-speed)

COPY FUNCTIONS

Max. original size: A3

Continuous copying: 1–999

Zoom range: 25–400 % in 1 % steps

Preset magnification ratios: 5R/5E

Digital features: scan-once-print-many, electronic sort copy, rotate sort copy*, automatic paper selection, duplex copying**, combined inch/metric copying, layout mode (2-in-1, 4-in-1), program key mode

*Additional paper feeder PF-480 is required

**Additional duplex unit DU-480 is required

Density adjustment: Auto, manual: 7 steps

Image adjustments: Text + photo, text, photo

SCAN FUNCTIONS

Scan functionality

Scan-to-PC, scan-to-email, images network TWAIN

Scan speed: up to 22 images per minute (600 dpi/A4)

Original type: text, photo, text + photo

Max. scan size: A3

Scan resolution

600 dpi, 400 dpi, 300 dpi, 200 dpi (256 greyscales)

Image format: PDF, JPG, BMP, TIFF

CONSUMABLES

TK-4105 Toner-kit: Microfine toner for 15,000 pages with 6% A4 coverage capacity of starter toner for 3,000 pages with 6% A4 coverage

OPTIONS

Paper handling

DP-480 Document processor: (reversing) 50 sheets, duplex scan, 45–120 g/m², A3-A5R, Folio, Ledger-statement-R.

PF-480 Paper feeder: 300 sheets, 64–105 g/m², A3-A5R, Folio, Ledger-statement-R (max. three PF-480 can be added to the basis system)

DU-480 Duplex unit: 64–105 g/m², A3-A5R, Folio, Ledger-statement-R

Others

Platen cover (H):

Cabinet: wooden/metal with desk storage capacity including castors (wheels)*

CB-480L (low/wooden)

CB-480H (high/wooden)

CB-481L (low/metal)

CB-481H (high/metal)

*Max. one cassette can be configured for high type cabinet

