



> PRINT > COPY > SCAN > FAX

TASKalfa 1801
TASKalfa 2201

B/W MULTIFUNCTIONALS
FOR A3 FORMAT

THE COMPACT BUSINESS ALL-ROUNDERS.



In spite of their compactness, the new TASKalfa 1801 and 2201 have the means to get you through a busy day. The b/w prints and copies they produce are of exceptional quality with an image resolution of 600 dpi and a grey-scale of 256 shades. Their standard colour scan and the optional network print and fax functions provide you with the flexibility you need, and can be accessed via the easy-to-use control panel. These devices are perfect for demanding offices with little space for their office equipment.

- > Up to 18 / 22 pages in A4 and 8 / 10 pages in A3 per minute
- > Standard print and colour scan functionality
- > 600-dpi laser technology with 256-greyscale copying for crisp text and realistic photos
- > Optional gigabit network interface and fax functionality
- > Standard paper capacity of 400 sheets (expandable to 1,300 sheets)
- > Long-life components for exceptional efficiency and reliability



The TASKalfa 1801/ 2201 incorporate extremely durable components that guarantee efficient and reliable operation to meet the demanding requirements of busy office environments. These devices provide long hardware maintenance cycles that keep your overall operating costs low and productivity high – whilst ensuring a minimum impact on the environment.

TASKalfa 1801 | TASKalfa 2201 GENERAL

Technology: KYOCERA Laser, Mono component

Engine speed (pages per minute)

TASKalfa 1801: Max.18/8 pages per minute A4/A3

TASKalfa 2201: Max. 22/10 pages per minute A4/A3

Resolution: 600 x 600 dpi, 256 greyscales

Warm-up time from power on

18.8 seconds or less from power on

Time to first page: 5.7 seconds or less

Dimensions (W x D x H): 565 x 527 x 485 mm

Weight: Main unit: approx. 26 kg

Power source: AC 220 ~ 240 V, 50/60 Hz

Power consumption

TASKalfa 1801:

Printing: 385 W

Standby: 75 W

Sleep mode: 1.54 W

TASKalfa 2201:

Printing: 415 W

Standby: 76 W

Sleep mode: 1.54 W

Noise (sound pressure level ISO 7779/ISO 9296)

Copying: 62.0 dB(A); standby: 40 dB(A)

Safety standards: GS, TÜV, CE

This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity

300-sheet universal paper cassette, 64 – 105 g/m², A3, A4, A5, Ledger, Letter, Legal

100-sheet multi-purpose tray, 45 – 160 g/m², A3, A4, A5, A6, Ledger, Letter, Legal

Max. input capacity with options: 1,300 sheets

Output capacity: 250 sheets face-down

PRINT FUNCTIONS

CPU: ARM v5 base core equivalent, 500 MHz

Memory: standard max. 256 MB

Operating systems: Host-based printing system for all current windows operating systems

Standard Interface: USB 2.0 (Hi-speed)

COPY FUNCTIONS

Max. original size: A3

Continuous copying: 1 – 999

Zoom range: 25 – 400 % in 1 % steps

Preset magnification ratios: 5 Reductions / 5 Enlargements

Digital features: scan-once-print-many, electronic sort copy, rotate sort copy*, automatic paper selection, duplex copying*, combined inch/metric copying, layout mode (2-in-1, 4-in-1), program key mode

*Additional paper feeder PF-480 is required

**Additional duplex unit DU-480 is required

Density adjustment: Auto, manual: 7 steps

Image adjustments: Text + photo, text, photo

SCAN FUNCTIONS

Scan functionality

Scan-to-PC, scan-to-email, images network TWAIN

Scan speed: up to 22 images per minute (600 dpi / A4)

Original type: text, photo, text + photo

Max. scan size: A3

Scan resolution

600 dpi, 400 dpi, 300 dpi, 200 dpi (256 greyscales)

Image format: PDF, JPG, BMP, TIFF

FAX FUNCTIONS (OPTIONAL)*

*Document processor DP-480 is required

Modem speed: max. 33.6 kbps

Compatibility: ITU-T SuperG3

Transmission speed: 4 seconds or less (MMR)

Fax resolution

Normal: 200 x 100 dpi, fine: 200 x 200 dpi, superfine: 200 x 400 dpi, halftone: 256 greyscales

Maximum original size: A3

Compression method: MMR, MR, MH

Fax features

Network faxing, rotate transmission, duplex fax reception, confidential, relay and bulletin board, transmission and reception, password checking transmission and reception, auto-reduction reception.

CONSUMABLES

TK-4105 Toner-kit: Microfine toner for 15,000 pages with 6 % A4 coverage; capacity of starter toner for 3,000 pages with 6 % A4 coverage

OPTIONS

Fax System (X)

Paper handling

DP-480 Document processor: (reversing) 50 sheets, duplex scan, 45 – 120 g/m², A3 – A5R, Folio, Ledger-statement-R.

PF-480 Paper feeder: 300 sheets, 64 – 105 g/m², A3 – A5R, Folio, Ledger-statement-R (max. three PF-480 can be added to the basis system)

DU-480 Duplex unit: 64 – 105 g/m², A3 – A5R, Folio, Ledger-statement-R

Others

IB-33: 10Base / 100BaseTX

Platen cover (H)

Cabinet: wooden/metal with desk storage capacity including castors (wheels)*

CB-480L (low/wooden)

CB-480H (high/wooden)

CB-481L (low/metal)

CB-481H (high/metal)

*Max. one cassette can be configured for high-type cabinet

