

FS-C8008N

►print ►copy ►scan ►fax

THE PRODUCTIVE WORKGROUP PRINTER OFFERING ALL THE ADDITIONAL BENEFITS OF COLOUR

- 31 pages per minute in b/w A4
8 pages per minute in full colour A4
- USB, parallel and network interface
as standard
- Universal cassette support from A5 to A3
- 1,150 sheets input as standard from 3 sources,
upgradable to 3,150 sheets from 7 sources
- ECOSYS technology: lowest cost per page in
its class for colour and b/w



Looking for a fast printer that can add a little flare to projects when it is needed most? The Kyocera FS-C8008N prints monochrome pages up to A3, at speed, and still has spare capacity for full colour A3 prints. With forward thinking ECOSYS technology you are ensured a low total cost of ownership, advanced paper handling capabilities and plenty of network connection options. It stands at the ready for a workgroup connected by ideas of every colour.



FS-C8008N

Colour/Monochrome A3 Printer

The ECOSYS colour technology is based on extremely durable components. The drum, developer and fuser of the FS-C8008N are designed for 300,000 pages. As toner is the only consumable required, ECOSYS printers operate with the lowest cost per page in their class, and they are particularly environmentally friendly. Thanks to their modular system and flexible paper options all ECOSYS printers can be configured to meet your exact requirements.

System platform

The FS-C8008N delivers outstanding network connectivity and problem-free system administration. Kyocera's single-platform technology means that the same driver can be used for every Kyocera PCL/PostScript print device in the network: from single-user desktop printers to high-end multifunctional systems. Only Kyocera offers this effortless combination of IT sophistication and high-performance paper handling expertise.

GENERAL

Technology: Kyocera Colour ECOSYS, Laser
Engine speed: Max. 31/15 pages per minute A4/A3 in b/w mode, max. 8/4 pages per minute A4/A3 in full colour mode
Resolution: 600 x 600 dpi multi-bit technology for optimum colour output
Time to first page: 17 seconds or less in b/w, 28 seconds or less in colour
Warm-up time: 180 seconds or less from power on
Duty cycle: Max. 100,000 pages per month in b/w, max. 25,000 pages per month in colour
Power source: AC 220 ~ 240 V, 50/60 Hz
Power consumption: Printing: 803 W, Stand-by: 196 W, Power-Saving (ECOpower): 26 W
Noise (ISO 7779): Printing: 53 dB(A), Stand-by: 39 dB(A), Power-Saving (ECOpower): Immeasurably low
Dimensions (W x D x H): FS-C8008N (incl. PF-30A or PD-800): 590 x 585 x 673 mm, PF-30A/PD-800: 560 x 566 x 251 mm
Weight: FS-C8008N (incl. PF-30A): Approx. 95 kg, FS-C8008N (incl. PD-800): Approx. 98 kg, PF-30A: Approx. 19 kg, PD-800: Approx. 22 kg
Certifications: TÜV/GS, CE
This product is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by Kyocera under normal environmental conditions.

Input capacity: 2 x 500-sheet universal paper cassette, 64-90 g/m², A3, A4, A5, B4, B5, Letter, Legal, Custom (148 x 210 mm to 297 x 420 mm)
150-sheet multi-purpose tray, 64-220 g/m², A3, A4, A5, A6, B4, B5, Letter, Legal, Custom (80 x 148 mm to 310 x 458 mm), envelopes
2 x 500-sheet optional paper cassette, 60-90 g/m², A3, A4, A5, B4, B5, Letter, Legal, Custom (148 x 210 mm to 297 x 420 mm)
Max. 2 optional units, max. input capacity with options: 3,150 sheets
Output capacity: 500 sheets face-down with paper full sensor, 150 sheets face-up

CONTROLLER

Processor: PowerPC 750CX / 400 MHz
Memory: Standard 128 MB + ECOMemory, max. 640 MB, 2 additional DIMM slots (32, 64, 128, 256 MB)
Emulations: PCL6/PCL5c incl. PCL, KPDL 3 (PostScript 3 compatible), KC-GL (HP-GL 7550A), PDF direct print
Controller language: PRESCRIBE IIc
Fonts: 80 outline fonts (PCL5c), 1 bitmap font, 136 outline fonts (KPDL 3), 45 types of one-dimensional barcodes plus two-dimensional barcode PDF-417
Print features: eMPS – for quick copy, proof and hold, private print, job storage and job management functionality with optional HD-4 Hard disk

Your Kyocera Business Partner:

PRESCRIBE IIe/IIc

With the Kyocera page design and control language PRESCRIBE IIe/IIc, even complex graphics, logos and forms (even multipart forms) can be created independently of the system and saved and updated in the printer. Consequently, integration into print files no longer applies. They are only accessed as required and therefore relieve the load on the network.

Typefaces and barcodes

The 136 scalable PostScript fonts provide high flexibility for all applications. A total of 45 integrated barcodes including hash totals are computed automatically by the printer and printed in the desired size, alignment and position.

INTERFACE

Standard interface: High speed bi-directional parallel (IEEE 1284), USB 2.0 (Full Speed), Fast Ethernet 10/100Base-TX, KUJO-LV slot for optional 2nd parallel interface or RS-232C serial interface or network interface card
Multiple interface connection (MIC): Allows simultaneous data transfer via up to four interfaces, with each interface having its own virtual printer.

OPTIONS

Paper handling
PF-30A Paper feeder (max. 2 units): 500 sheets each, 60-90 g/m², A3, A4, A5, B4, B5, Letter, Legal, Custom (148 x 210 mm to 297 x 420 mm)
PD-800 Duplex unit with paper feeder: 500 sheets, 60-90 g/m², A3, A4, A5, B4, B5, Letter, Legal, Custom (148 x 210 mm to 297 x 420 mm)
ST-30 Stacker: 3,000 sheets face-up/face-down and document separation, 60-200 g/m², A3, A4, A5, B4, B5, Letter, Legal, Custom (148 x 210 mm to 297 x 420 mm)
DF-31 Document finisher: 2,000 sheets face-up/face-down with document separation and stapler for 20 sheets
SO-30 Sorter: 9 bins for 200 sheets each face-down, 1 bin for 100 sheets face-up incl. mailbox and stacker function
CA-31B Caster: Set of wheels

Memory
Printer memory expansion: 2 slots (32, 64, 128, 256 MB DIMM)
CompactFlash® card: 1 slot (8, 16, 32, 64 MB), forms, fonts, logos, macro storage
HD-4 Hard disk: 20 GB, storage of data, forms, fonts + eMPS

Optional interface
IB-21E Network card: 10/100Base-TX
SB-50 Network card: 10Base-FL, FibreLink
SB-60 Network card: TokenRing STP/UTP
SB-70 Network card: Wireless LAN – IEEE 802.11b
SB-110FX Network card: 10/100Base-TX, 100Base-FX, FibreOptic
SB-140 Network card: 10Base-2, 10/100Base-TX
SB-80 Parallel interface: 2nd parallel interface – IEEE 1284
IB-11 Serial interface: RS-232C serial interface (max. 115.2kbps)

CONSUMABLES

TK-800Y Toner-kit: Microfine toner yellow for 10,000 pages with 5 % coverage (A4)
TK-800M Toner-kit: Microfine toner magenta for 10,000 pages with 5 % coverage (A4)
TK-800C Toner-kit: Microfine toner cyan for 10,000 pages with 5 % coverage (A4)
TK-800K Toner-kit: Microfine toner black for 25,000 pages with 5 % coverage (A4)

KM-NET Viewer

KM-NET Viewer is an advanced network management software tool that is compatible with all Kyocera printers and multifunctional products as well as those of other vendors by using the standardized protocol SNMP. The settings of all printers on the network can be checked visually and amended from any Windows PC. KM-NET Viewer also acts as a valuable, real-time early warning system by sending eMail-Messages.

CompactFlash® card

The CompactFlash® card offers abundant storage space for typefaces, logos, standard forms and signatures as well as individual API or PRESCRIBE macros.

Hard disk

The optional hard disk offers even more efficient document management. At the same time it enables the management of print data with eMPS functions such as quick copy, proof and hold, private print and job storage.

WARRANTY

2-year warranty as standard. Kyocera guarantees the drums for 3 years or 600,000 images and developers for 3 years or 300,000 pages (whichever occurs sooner), provided each printer is used and cleaned in accordance with the service instructions.

KYO LIFE The up to 5-year on-site warranty extension for printer and options.



Select your options to suit your needs:



PF-30A Paper feeder

Product depicted includes optional extras

Kyocera Mita Europe B.V., Hoeksteen 40, 2132 MS Hoofddorp, The Netherlands, Tel +31 (0) 20 65 40 000, Fax +31 (0) 20 65 31 256, www.kyoceramita-europe.com, info@kyoceramita-europe.com
Kyocera Mita Corporation, 2-28, 1-Chome, Tamatsukuri, Chuo-Ku, Osaka 540-8585, Japan, www.kyoceramita.com

Kyocera does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

