

FS-1018MFP

discover

► network printing/scanning
and copying performance
for your whole workgroup



- 18 pages per minute in A4 with Fast 1200 dpi
- Time to first print: less than 8 seconds
- Standard network connectivity for printing and colour scanning
- 300-sheet paper capacity as standard, upgradeable to 550 sheets
- Low total cost of ownership

Product depicted includes optional extras

► print ► copy ► scan ► fax

Combining outstanding productivity with cost-effective ECOSYS technology, the Kyocera FS-1018MFP sets a new benchmark for compact multifunctional solutions. Let your entire workgroup effortlessly print and scan via the network and copy documents as well. With colour scanning you can send colour documents and highlight the points of attention in colour. The FS-1018MFP meets the challenges of the demanding business environment producing 18 A4 ppm at 1200 dpi quality. High volume jobs are handled with ease. Adding the optional document processor and the optional 250-sheet paper feeder increases efficiency even further. With its large five-line LCD display panel, compact ergonomic design and low total cost of ownership, the FS-1018MFP is ready to transform your office workflow from the very first day.



FS-1018MFP

Monochrome A4 multifunctional

ECOSYS technology is based on extremely durable components. The drum and fuser of the FS-1018MFP are designed to last for 100,000 pages. As toner is the only consumable required, ECOSYS products operate with the lowest cost per page in their class and they are particularly environmentally friendly. Thanks to their modular system and flexible paper options all ECOSYS products can be configured to meet your exact requirements.

GENERAL

Technology: Kyocera Laser, Mono component
Type: Desktop
Engine speed: Max. 18 pages A4 per minute
Resolution: 600 x 600 dpi, 256 greyscales (scan/copy), Fast 1200 dpi resolution (print)
Time to first copy: approx. 10 seconds
Time to first print: 8 seconds or less
Warm-up time: 30 seconds or less
Duty cycle: Max. 10,000 pages per month
Power Source: AC 220 V ~ 240 V, 50/60 Hz
Power Consumption: Printing: 409 W, Stand-by: 76 W, Low power mode: 43 W
Noise (ISO 7779): Printing: 65 dB (A), Stand-by: 43 dB (A)
Dimensions (W x D x H): 496 x 421 x 385 mm
Weight: Approx. 14.5 kg
Certification: GS/TÜV/CE
This product is produced according to the quality norm ISO 9001 and the environmental guidelines ISO 14001.

PAPER HANDLING

All mentioned paper capacities are based on a paper thickness of max. 0.11 mm. Please use paper recommended by Kyocera Mita under normal environmental conditions.

Input capacity: 250-sheet universal feeder, 60-105 g/m², A4, B5, A5, A6, Letter, Legal, Folio, 50-sheet multi-purpose tray, 60-163 g/m², A4, B5, A5, A6, Letter, Legal, Folio, Custom (105 x 148 - 216 x 356 mm), Envelopes, Max. capacity 550 sheets
Output capacity: 150-sheet face-down, 30-sheet face-up

COPY FUNCTIONS

Max. original size: A4, Folio
Continuous copy: 1 - 999 copies
Memory capacity: 96 MB RAM standard, Max. 320 MB, 1 additional DIMM slot (64, 128, 256 MB)
Zoom range: 50 - 200 % in 1 % steps
Present magnification ratios: 6R / 4E
Exposure mode: Auto, Manual: 7 steps
Image adjustments: Text + Photo, Text, Photo
Digital copy features: Scan-once-print-many, electronic sort, auto start, auto cassette change, density adjustment, paper size selection, layout mode (2-in-1, 4-in-1), ECOcopy mode, job reservation

PRINT FUNCTIONS

Processor: PowerPC 750CXR
Memory: 96 MB RAM standard, Max. 320 MB, 1 additional DIMM slot (64, 128, 256 MB)
Emulations: PCL 6/PCL 5e incl. PJI, KPDL 3 (PostScript 3 compatible) with Automatic Emulation Sensing (AES), Line Printer, IBM Proprinter X24E, Epson LQ-850, Diablo 630
Controller language: PRESCRIBE
Fonts: 80 outline fonts (PCL, KPDL2), 1 Bitmap font
Print features: PDF Direct Printing

System Platform

The FS-1018MFP delivers outstanding network connectivity and problem-free system administration. Kyocera's single platform technology means that the same driver can be used for every Kyocera print device in the network: from single-user desktop printers to high-end multifunctional systems. Only Kyocera offers this effortless combination of IT sophistication and high-performance paper handling expertise.

PRESCRIBE IIe

With the Kyocera page design and control language PRESCRIBE IIe, even complex graphics, logos and forms (and multipart forms) can be created independently of the system and saved and updated in the printer. Consequently, integration into print files no longer applies. They are only accessed as required and therefore relieve the load on the network.

INTERFACES

Standard interface: Fast Ethernet 10/100 base TX, High Speed bi-directional parallel (IEEE 1284), USB 2.0 (High-Speed)
Multiple interface connection (MIC): Allows for simultaneous data transfer via up to three interfaces, with each interface having its own virtual printer.

SCAN FUNCTIONS

Functionality: Scan-to-e-mail
Scan Speed: Max. 18 originals per minute (600 dpi / A4, B&W)
Original type: Text, photo, text + photo and OCR
Maximum scan size: A4, Folio
Scan resolution: 600, 400, 300, 200 dpi (256 greyscales)
Applicable PC: IBM PC/AT compatible
Applicable OS: Windows 98, 98SE, Me, NT4.0, 2000, XP
Interface: 10/100Base-TX
Network protocol: TCP/IP
Compression format: MMR/JPEG
Image format: PDF, TIFF (B&W only), JPEG (colour only)

OPTIONS

Paper handling
DP-100 Document Feeder: 50 sheets, 50-120 g/m², A5R - A4R, Folio,
PF-17 paper feeder: 250 sheets, 60 -105 g/m², A4, B5, A5, Letter, Legal, Folio, Custom (148 x 210 mm to 216 x 297 mm),
CB-100 Cabinet: Wooden desk with storage capacity, including castors (wheels)

Memory: 64, 128, 256 MB (1 additional DIMM slot)

Typefaces and barcodes

The 80 scalable PostScript fonts provide high flexibility for all applications. A total of 45 integrated barcodes including hash totals are computed automatically by the printer and printed in the desired size, alignment and position.

KM-NET VIEWER

KM-NET VIEWER is an advanced network management software tool that is compatible with all Kyocera printers and multifunctional products as well as those of other vendors by using the standardized protocol SNMP. The settings of all printers on the network can be checked visually and amended from any Windows PC. KM-NET VIEWER also acts as a valuable, real-time early warning system by sending e-mail messages.

CONSUMABLES

TK-18 Toner-Kit: Microfine toner for 7,200 pages with 5 % coverage (ISO 10561B)

Capacity of starter toner for 3,600 pages with 5 % coverage (ISO 10561B)

WARRANTY

2-year warranty as standard. Kyocera Mita guarantees the drum for 3 years or 100,000 pages (whichever occurs sooner), provided each printer is used and cleaned in accordance with the service instructions.



Select your options to suit your needs:

DP-100 Document Processor

PF-17 Paper Feeder

CB-100 Cabinet

Product depicted includes optional extras



Your Kyocera Mita Business Partner:

Kyocera Mita Europe B.V., Hoeksteen 40, 2132 MS Hoofddorp, The Netherlands,
Tel +31 (0) 20 65 40 000, Fax +31 (0) 20 65 31 256, www.kyoceramita-europe.com, info@kyoceramita-europe.com

FS-1018MFP - English - 8DSE1018. Kyocera Mita does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

