

# FS-C5030N

►print ►copy ►scan ►fax

## THE COLOUR CHOICE TO KEEP YOU IN THE BLACK



- 24ppm in A4 colour and b/w
- First page in 12 seconds
- 500-sheet paper cassette, optional 3 x 500-sheet cassettes, optional duplex
- Parallel, USB 2.0 High Speed, 10/100Base-T as standard
- 128 MB standard RAM, upgradeable to 1024 MB
- Compact design with minimum footprint
- ECOSYS long-life technology

Are your colour printers putting a big financial strain on your company? Then take a look at the FS-C5030N from Kyocera. This speedy and compact printer is perfect for workgroups looking for a higher print volume combined with lower running costs. Our unique ECOSYS technology has been delivering b/w printers with reduced costs for more than a decade. And this innovative system is also available for colour. In addition, this network-ready device can be shared from day one and fits seamlessly into any office environment. Talk to Kyocera about making the right colour choice and avoiding grey hairs.



# FS-C5030N

## Colour/Monochrome A4 Printer

The ECOSYS colour technology is based on extremely durable components. Due to the fact that toner is the only consumable required, ECOSYS printers operate with the lowest cost per page in their class, and they are particularly environmentally friendly. Thanks to their numerous system, paper options and modularity, all ECOSYS printers can develop to meet further requirements.

### System platform

The FS-C5030N delivers outstanding network connectivity and problem-free system administration. Kyocera's single platform technology means that the same driver can be used for every Kyocera PCL/PostScript print device in the network: from single-user desktop printers to high-end multifunctional systems. Only Kyocera offers this effortless combination of IT sophistication and high-performance paper handling expertise.

### GENERAL

**Technology:** Kyocera Colour ECOSYS  
**Type:** Desktop  
**Engine speed:** Max. 24 pages per minute b/w and full colour  
 Up to 24 images per minute in duplex mode (optional)  
**Resolution:** 600 x 600 dpi  
 Multi-Bit Technology for optimum colour output  
**Time to first page:** 12 seconds or less  
**Warm-up time:** 80 seconds or less from power on  
**Duty cycle:** Max. 85,000 pages per month (A4)  
**Power source:** AC 220 ~ 240 V, 50/60 Hz  
**Power consumption:** Printing 551 W, Stand-by 180 W, Power-Saving (ECOpower) 21 W  
**Noise (ISO 7779):** Printing 55 dB(A), Stand-by 36 dB(A), Power-Saving (ECOpower): Immeasurably Low  
**Dimensions (W x D x H):** 345 x 470 x 385 mm  
**Weight:** Approx. 23 kg  
**Certification:** GS/TÜV/CE  
 This printer is produced according to the quality norm ISO 9001 and the environmental guidelines ISO 14001

### PAPER HANDLING

All mentioned paper capacities are based on a paper thickness of max. 0.11 mm. Please use paper recommended by Kyocera under normal environmental condition.

**Input capacity:** 500-sheet universal cassette, 60-105 g/m<sup>2</sup>, A4, B5, A5, Letter, Custom (148 x 210 – 216 x 356 mm), 100-sheet multi-purpose tray, 60-200 g/m<sup>2</sup>, A4, B5, A5, Letter, Legal, Custom (70 x 148 – 216 x 297 mm), Max. 2,100 sheets  
**Output capacity:** 250-sheet face-down with paper full sensor, Face-up output with optional PT-300

With the Kyocera page design and control language PRESCRIBE IIe/IIc, even complex graphics, logos and forms (even multipart forms) can be created independently of the system and saved and updated in the print controller. Consequently, integration into print files no longer applies. They are only accessed as required and therefore relieve the load on the network.

### Typefaces and barcodes

The 136 scalable PostScript fonts provide high flexibility for all applications. A total of 45 integrated barcodes including hash totals are computed automatically by the printer and printed in the desired size, alignment and position.

### CONTROLLER

**Processor:** PowerPC750FX/600 MHz  
**Memory:** 128 MB RAM + ECOMemory, Max. 1,024 MB in 2 DIMM slots  
**Emulations:** PCL 6 (PCL 5c/PCL-XL), KPDL 3 (PostScript 3 compatible) with Automatic Emulation Sensing (AES), PDF Direct Print  
**Controller language:** PRESCRIBE IIc  
**Fonts:** 80 outline fonts (PCL 6: PCL 5c/PCL-XL), 136 outline fonts (KPDL 3); 1 bitmap font; 45 types of one-dimensional barcodes, plus 1 type of two-dimensional barcode (PDF-417).  
 Downloadable fonts: Kyocera, PCL & TrueType format, Type 1 + 3 font format  
**Print features:** eMPS – for quick copy, proof and hold, private print, job storage and job management functionality with hard disk

### INTERFACE

**Standard interface:** High speed bi-directional parallel (IEEE 1284), USB 2.0 (Hi-Speed), Fast Ethernet 10/100Base-TX, KUIO-LV Option-Interface Slot  
**Multiple interface connection (MIC):** Allows for simultaneous data transfer via up to four (MIC) interfaces, with each interface having its own virtual printer.

### CONSUMABLES

**Toner-Kit TK-510K:** Microfine Toner Black for 8,000 pages with 5 % A4 coverage (ISO 10561B).  
**Toner-Kit TK-510C:** Microfine Toner Cyan for 8,000 pages with 5 % A4 coverage (ISO 10561B).  
**Toner-Kit TK-510M:** Microfine Toner Magenta for 8,000 pages with 5 % A4 coverage (ISO 10561B).  
**Toner-Kit TK-510Y:** Microfine Toner Yellow for 8,000 pages with 5 % A4 coverage (ISO 10561B).  
 Capacity of starter toner is 4,000 pages with 5 % coverage (ISO 10561B).

### CompactFlash® card

The CompactFlash® card offers abundant storage space for typefaces, logos, standard forms and signatures as well as individual API or PRESCRIBE macros.

### Hard disk

The optional hard disk offers even more efficient document management. At the same time it enables the management of print data with eMPS functions such as quick copy, proof and hold, private print and job storage.

### KM-NET Viewer

KM-NET Viewer is an advanced network management software tool that is compatible with all Kyocera printers and multifunctional products as well as those of other vendors by using the standardized protocol SNMP. The settings of all print devices on the network can be checked visually and amended from any Windows PC. KM-NET Viewer also acts as a valuable, real-time early warning system by sending eMail Messages to users/administrators.

### OPTIONS

**Paper handling**  
**PF-60 Paper Feeder:** 500-sheet, 60-105 g/m<sup>2</sup>, A4, B5, A5, Letter, Legal, Custom (148 x 210 – 216 x 356 mm) Max. 3 PF-60  
**EF-60 Envelope Feeder:** 70 standard envelopes / 100 air mail envelopes, A6-C5  
**DU-301 Duplex Unit:** Double-sided printing, 60-105 g/m<sup>2</sup>, A4, B5, A5, Letter, Legal, Custom (148 x 210 mm – 216 x 356 mm)  
**PT-301 Paper Tray:** Face-up paper output tray

**Memory**  
**Printer Memory:** 2 slots (64, 128, 256, 512 MB DIMM)  
**CompactFlash® card:** 1 slot (16, 32, 64 MB) for printing forms, fonts, logos, macro storage.  
**Hard disk HD-4:** 20 GB HDD for easy document management  
**OCR-2:** Font ROM with OCR-A and OCR-B font types

**Optional interface**  
**SB-80 Parallel Interface:** 2nd Parallel Interface (IEEE 1284)  
**IB-11 Serial Interface:** RS-232C Serial Interface (up to 115.2kbps)  
**IB-21E Network card:** 10Base-T/100Base-TX  
**SB-50 Network card:** 10Base-FL, FibreLink  
**SB-60 Network card:** TokenRing STP/UTP  
**SB-70 Network card:** Wireless LAN – IEEE 802.11b  
**SB-110FX Network card:** 10Base-T/100Base-TX/100Base-FX, FibreOptic  
**SB-140 Network card:** 10Base-2/10Base-T/100Base-TX

### WARRANTY

2-year warranty as standard. Kyocera guarantees the drums and developers for 3-year or 200,000 pages (whichever occurs sooner), provided each printer is used and cleaned in accordance with the service instructions.

**KYO LIFE** The up to 5-year on-site warranty extension for printer and options.



Your Kyocera Business Partner:

Kyocera Mita Europe B.V., Hoeksteen 40, 2132 MS Hoofddorp, The Netherlands, Tel +31 (0) 20 65 40 000, Fax +31 (0) 20 65 31 256, www.kyoceramita-europe.com, info@kyoceramita-europe.com  
 Kyocera Mita Corporation, 2-28, 1-Chome, Tamatsukuri, Chuo-Ku, Osaka 540-8585, Japan, www.kyoceramita.com

Kyocera does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

