

FS-9520DN

►print ►copy ►scan ►fax

THE VERSATILE HIGH SPEED A3 DEPARTMENTAL PRINTER



- 51 pages per minute in A4 with 1,200 dpi quality
26 pages per minute in A3 with 1,200 dpi quality
- Automatic duplex and network-ready as standard
- 8 emulations including PCL6, PS 3 and PDF direct printing
- Outstanding finishing options up to high volume
- Warm-up time: only 25 seconds from power on
- Lowest cost per page in its class

Product depicted includes optional extras

At a lightning-fast 51 pages per minute on A4, this high speed machine is the flagship of the Kyocera monochrome printer range. With duplex and network functionality as standard the FS-9520DN offers a perfect base for high volume departmental printing. Choose between three optional finishers for entry level finishing, booklet finishing or high volume finishing. Meet your stapling, punching or booklet production requirements with the range of powerful finishers. The high speed controller with its 500 MHz and 64 MB RAM ensures that the potential of the FS-9520DN can be utilised at its best. Lowest cost per page in its class and cost savings from the beginning result in an unbeatably low TCO.



FS-9520DN

Monochrome A3 Departmental Printer

The ECOSYS technology is based on extremely durable components. The drum, developer and fuser of the FS-9520DN are designed for 500,000 pages. As toner is the only consumable required, ECOLaser printers operate with the lowest cost per page in their class, and they are particularly environmentally friendly. Thanks to their modular system and flexible paper options all ECOLaser printers can be configured to meet your exact requirements.

System platform

The FS-9520DN delivers outstanding network connectivity and problem-free system administration. Kyocera's single platform technology means that the same driver can be used for every Kyocera PCL/PostScript print device in the network: from single-user desktop printers to high-end multifunctional systems. Only Kyocera offers this effortless combination of IT sophistication and high-performance paper handling expertise. Duplex and network functionality is standard in the FS-9520DN.

GENERAL

Technology: Kyocera ECOSYS, Laser
Engine speed: Max. 51 pages per minute A4, max. 26 pages per minute A3
Resolution: 1,200 dpi quality (1,800 x 600)
Time to first page: 5 seconds
Warm-up time: 25 seconds from power on
Duty cycle: Max. 300,000 pages per month, average 55,000 pages per month
Power source: AC 220 ~ 240 V, 50/60 Hz
Power consumption: Printing: 940 W, Stand-by: 160 W, Power-Saving (ECOpower): 12 W
Noise (ISO 7779): Printing: 54 dB(A), Stand-by: 39 dB(A), Power-Saving (ECOpower): Immeasurably low
Dimensions (W x D x H): 585 x 639 x 615 mm
Weight: Main unit: Approx. 67 kg
Certifications: TÜV/GS, CE, PTS
This product is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by Kyocera under normal environmental condition.

Input capacity: 2 x 500-sheet universal paper cassette, 60-105 g/m², A3, A4, A4-R, A5, B4, B5, B5-R, Letter, Letter-R, Legal, Ledger, Folio, STMT
200-sheet multi-purpose tray, 60-200 g/m², A3-A6R, Custom (88 x 148 mm to 297 x 450 mm)
Max. input capacity with optional paper feeder PF-75: 4,200 sheets
Duplex as standard
Output capacity: 500 sheets face-down

CONTROLLER

Processor: PowerPC 750CX / 500 MHz
Memory: Standard 64 MB + ECOMemory, max. 576 MB (2 DIMM slots)
Emulations: PCL6/PCL5e incl. P1L, KPDL 3 (PostScript 3 compatible), PDF direct print, automatic emulation sensing (AES), KC-GL (HP-7550A), Line Printer, IBM Proprinter X24E, Epson LQ-850, Diablo 630
Controller language: PRESCRIBE IIe
Fonts: 80 outline fonts (PCL), 136 PostScript Fonts, 1 bitmap font, 45 types of one-dimensional barcodes, plus two-dimensional barcode PDF-417
Downloadable fonts: Kyocera, PCL + TrueType format, Type 1 + 3 format
Print features: eMPS – job management functionality with optional hard disk HD-4 for quick copy, proof and hold, private print and job storage

PRESCRIBE IIe

With the Kyocera page design and control language PRESCRIBE IIe, even complex graphics, logos and forms (even multipart forms) can be created independently of the system and saved and updated in the printer. Consequently, integration into print files no longer applies. They are only accessed as required and therefore relieve the load on the network.

Typefaces and barcodes

The 136 scalable high quality PostScript fonts provide high flexibility for all applications. A total of 45 integrated barcodes including hash totals are computed automatically by the printer and printed in the desired size, alignment and position.

INTERFACE

Standard interface: Fast Ethernet 10/100Base-TX, High speed bi-directional parallel (IEEE 1284), USB 2.0 (Hi-Speed), KUJO-LV option interface slot
Multiple interface connection (MIC): Allows simultaneous data transfer via up to four interfaces, with each interface having its own virtual printer.

OPTIONS

Paper handling
PF-70 Paper feeder: 2 x 500 sheets, 60-105 g/m², A3, A4, A4-R, A5, B4, B5, B5-R, Letter, Letter-R, Legal, Ledger, Folio, STMT
PF-75 Paper feeder: Max. 3,000 sheets, 60-105 g/m², A4, B5, Letter
DF-71E Document finisher + AK-71P: 250 sheets face-up, max. 3,000 sheets A4 or 1,500 sheets A3 face-down, max. 50 sheets A4 or 30 sheets A3 stapling at 3 positions, 2 or 4 hole punch
M-2107 Mailbox: 7 bins x 100 sheets mailbox, A3-A5R, for DF-71E
DF-73 Document finisher: Max. 1,000 sheets, one position stapling max. 30 sheets
DF-75R Document finisher + RA-1 + AK-71P: Max. 1,000 sheets A4 or 500 sheets A3, staple max. 50 sheets A4 or 30 sheets A3, stapling at 3 positions, Booklet folding and stapling max. 40 pages (10 sheet)
PH-2B/PH-2C/PH-2D Punch unit for DF-75R: 2-hole/4-hole/Swedish type
CB-70 Cabinet (W x D x H): 590 x 600 x 320 mm desk with storage capacity

Memory
Printer memory: 2 slots (16, 32, 64, 128 or 256 MB DIMM)
CompactFlash® card: 1 slot (8, 16, 32, 64 MB), forms, fonts, logos, macro storage
HD-4 Hard disk: 20 GB, storage of data, forms, fonts and job management

Optional interface
IB-21E Network card: 10Base-T/100Base-TX
SB-50 Network card: 10Base-FL, FibreLink
SB-60 Network card: TokenRing STP/UTP
SB-70 Network card: Wireless LAN – IEEE 802.11b
SB-110FX Network card: 10Base-T/100Base-TX/100Base-FX, FibreOptic
SB-140 Network card: 10Base-2/10-Base-T/100Base-TX
SB-80 Parallel interface: 2nd parallel interface – IEEE 1284
IB-11 Serial interface: RS-232C serial interface (max. 115.2 kbps)

KM-NET Viewer

KM-NET Viewer is an advanced network management software tool that is compatible with all Kyocera printers and multifunctional products as well as those of other vendors by using the standardized protocol SNMP. The settings of all printers on the network can be checked visually and amended from any Windows PC. KM-NET Viewer also acts as a valuable, real-time early warning system by sending eMail-Messages.

CompactFlash® card

The CompactFlash® card offers abundant storage space for typefaces, logos, standard forms and signatures as well as individual API or PRESCRIBE macros.

Hard disk

The optional hard disk offers even more efficient document management. At the same time it enables the management of print data with eMPS functions such as quick copy, proof and hold, private print and job storage.

CONSUMABLES

TK-70 Toner-kit: Microfine toner for 40,000 pages with 5% coverage (ISO 10561B) 70,000 pages according to Dr. Grauert letter (ISO 10561A)

Capacity of starter toner is 20,000 pages with 5% coverage (ISO 10561B)

WARRANTY

2-year warranty as standard. Kyocera guarantees the drum and developer for 3-year or 500,000 pages (whichever occurs sooner), provided each printer is used and cleaned in accordance with the service instructions.

The up to 5-year on-site warranty extension for printer and options. The warranty is limited to 2 million pages (3 million pages with KYOLife).

KYO LIFE

MODEL CONFIGURATIONS

FS-9520DN/E: FS-9520DN + PF-70 + AK-71P + DF-73
FS-9520DN/B: FS-9520DN + PF-70 + AK-71P + DF-75 + RA-1
FS-9520DN/D: FS-9520DN + PF-75 + AK-71P + DF-71E + M-2107



Select your options to suit your needs:

Document
finisher (DF-75R)



Paper
feeder (PF-75)

Product depicted includes optional extras

Your Kyocera Business Partner:

Kyocera Mita Europe B.V., Hoeksteen 40, 2132 MS Hoofddorp, The Netherlands, Tel +31 (0) 20 65 40 000, Fax +31 (0) 20 65 31 256, www.kyoceramita-europe.com, info@kyoceramita-europe.com
Kyocera Mita Corporation, 2-28, 1-Chome, Tamatsukuri, Chuo-Ku, Osaka 540-8585, Japan, www.kyoceramita.com

Kyocera does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

